

# AS364

Fire Sounder, Multi Tone, Deep Base

## General

---

The AS364 is a general purpose electronic sounder for fire alarm applications. Which features a special base containing all wiring connections and allow for easy removal/placement of the sounder.

## Easy and Fast Installation

---

The AS364 alarm sounder allows faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these sounders use a deep base version of the TimeSaver™ base from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

## Efficient and versatile

---

The AS364 provide high sound output at a low current, thus reducing power requirements and system cost. The AS364 sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation. With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second tone, is available if extra wires are installed in the sounder circuit.

The mechanism for locking the sounder to the base, can be activated if required. Once activated, a special tool is required to remove the sounder from the base.



## Standard Features

---

- High sound output
- Low current consumption
- 32 Tones user selectable
- Automatic synchronisation
- Volume control
- Anti-Tamper locking mechanism
- Deep mouting base
- Wiring directly to base
- Two stage alarm
- VdS Approved

# AS364

## Fire Sounder, Multi Tone, Deep Base

### Specifications

<b>Electrical</b>	
Current consumption	4 - 41mA @ 24 VDC
<b>Sounder</b>	
Selectable tones	32
<b>General</b>	
Line monitoring	polarised input
<b>Physical</b>	
Physical dimensions	100 x 104 mm (Ø x D)
Net weight	250 g
Colour	Red
Material	High impact polycarbonate
<b>Environmental</b>	
Operating temperature	-25 to +70°C
Environment	Indoor, Outdoor
IP rating	IP65
<b>Standards &amp; regulation</b>	
Certification	EN54-3
<b>Operation</b>	
	Continuous
<b>Supply voltage</b>	
EN54-3 / fire applications	17 - 60 VDC
non-fire applications	9 - 60 VDC
<b>Sound output @ 1 metre</b> (see tone table in manual)	
	94 to 106dB(A)
<b>Automatic synchronisation</b>	
	Phased start

### Ordering Information

Part No.	Description
AS364	Fire Sounder, Multi Tone, Deep Base
AS363	Fire Sounder, Multi Tone, Shallow Base
AS363W	Fire Sounder, Multi Tone, Shallow Base, White
AS363M	Sounder, Multi Tone, Shallow Base, Mains Powered
AS364W	Fire Sounder, Multi Tone, Deep Base, White
AS364M	Sounder, Multi Tone, Deep Base, Mains Powered
AS366	Sounder-Beacon, Multi Tone, Shallow Base
AS366W	Sounder-beacon, multi tone, shallow base, white
AS367	Sounder-Beacon, Multi Tone, Deep Base
AS367W	Sounder-beacon, multi tone, deep base, white
AS368	Base Sounder, Multi Tone, Red
AS368W	Base Sounder, Multi Tone, White