

# AS374

Fire Sounder, Hazardous Area, Multi Tone, Horn

## General

---

The AS374 is a hazardous area electronic sounder for use in hazardous areas, to provide an audible warning signal in case of fire. It carries EExd IIC T4 rating, and has a marine grade aluminium housing with IP67 rating.

## Hazardous Area

---

The AS374 is ATEX approved with ExII 2G and EExd IIC T4 ratings. It is housed in marine grade aluminium, and offers IP67 ingress protection.

## Efficient and versatile

---

The AS374 provide a high sound output level, which ensures that it can be used indoor and outdoor. The AS374 sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation. This allows of the output level to be reduced, when the sounder is used indoors. With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second and third tone, is available if extra wires are installed in the sounder circuit.



## Standard Features

---

- ATEX approved
- EExd IIC T4 rating
- 32 Tones user selectable
- 2nd and 3rd stage alarm
- IP67
- High output

# AS374

Fire Sounder, Hazardous Area, Multi Tone, Horn

## Specifications

<b>Physical</b>	
Net weight	3.4 kg
Colour	Red
<b>Environmental</b>	
Operating temperature	-50 to +55°C
Environment	Exd, Indoor, Outdoor
IP rating	IP67
<b>Standards &amp; regulation</b>	
Certification	CENELEC/ATEX
<b>Operation</b>	
	Continuous
<b>Supply voltage</b>	
	24 VDC
<b>Current consumption</b>	
(see tone table in manual)	250mA typical
<b>Sound output @ 1 metre</b>	
(see tone table in manual)	up to 117dB(A)
<b>Number of tones</b>	
	32
<b>Housing</b>	
	Marine grade LM6 aluminium
<b>Ingress protection</b>	
	IP67
<b>Operating temperature</b>	
	-50°C to +55°C
<b>Dimensions (Ø x D)</b>	
	181 x 262 mm
<b>Weight</b>	
	3.4 Kg
<b>Color</b>	
	Red

## Ordering Information

Part No.	Description
AS374	Fire Sounder, Hazardous Area, Multi Tone, Horn