

AS374

Fire Sounder, Hazardous Area, Multi Tone, Horn

General

The AS374 is a hazardous area electronic sounder for use in hazardous areas, to provide an audible warning signal in case of fire. It carries EExd IIC T4 rating, and has a marine grade aluminium housing with IP67 rating.

Hazardous Area

The AS374 is ATEX approved with ExII 2G and EExd IIC T4 ratings. It is housed in marine grade aluminium, and offers IP67 ingress protection.

Efficient and versatile

The AS374 provide a high sound output level, which ensures that it can be used indoor and outdoor. The AS374 sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation. This allows of the output level to be reduced, when the sounder is used indoors. With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second and third tone, is available if extra wires are installed in the sounder circuit.



Standard Features

- ATEX approved
- EExd IIC T4 rating
- 32 Tones user selectable
- 2nd and 3rd stage alarm
- IP67
- High output

AS374

Fire Sounder, Hazardous Area, Multi Tone, Horn

Specifications

Physical	
Net weight	3.4 kg
Colour	Red
Environmental	
Operating temperature	-50 to +55°C
Environment	Exd, Indoor, Outdoor
IP rating	IP67
Standards & regulation	
Certification	CENELEC/ATEX
Operation	
	Continuous
Supply voltage	
	24 VDC
Current consumption	
(see tone table in manual)	250mA typical
Sound output @ 1 metre	
(see tone table in manual)	up to 117dB(A)
Number of tones	
	32
Housing	
	Marine grade LM6 aluminium
Ingress protection	
	IP67
Operating temperature	
	-50°C to +55°C
Dimensions (Ø x D)	
	181 x 262 mm
Weight	
	3.4 Kg
Color	
	Red

Ordering Information

Part No.	Description
AS374	Fire Sounder, Hazardous Area, Multi Tone, Horn