

## BS122N

Battery 12 V 2.3 Ah



### Standard Features

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

# BS122N

Battery 12 V 2.3 Ah

## Specifications

### Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	2.3 Ah
Internal approx. resistance	42 mOhm

### Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	0.69 A
Max. discharge current	11.5 A

### Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

### General

Product type	Sealed lead acid battery
--------------	--------------------------

### Physical

Physical dimensions	178 x 34 x 60 mm
Net weight	1.061 kg
Material	ABS
Terminal type	Fast-on 4.8 mm

### Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

### Standards & regulation

Compliance	CE, RoHS 2, WEEE
Certification	VdS

## Ordering Information

Part No.	Description
BS122N	Battery 12 V 2.3 Ah