

BS127N

Battery 12 V 7.2 Ah (for 2010-1/-2 fire panels only, use BS127N-A for all



Standard Features

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS127N

Battery 12 V 7.2 Ah (for 2010-1/-2 fire panels only, use BS127N-A for all

Specifications

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	0 to 10 Ah
Internal approx. resistance	21 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC @ +20°C
Max. charge current	2.16 A
Max. discharge current	35 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

General

Product type	Sealed lead acid battery
--------------	--------------------------

Physical

Physical dimensions	151 x 94 x 65 mm
Net weight	2.678 kg
Shipping weight	2.678 kg
Material	ABS
Terminal type	Fast-on 4.8 mm

Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Standards & regulation

Compliance	RoHS 2, WEEE
Certification	VdS

Ordering Information

Part No.	Description
BS127NS3	Battery 12V 7.2 Ah
BS127N	Battery 12 V 7.2 Ah (for 2010-1/-2 fire panels only, use BS127N-A for all other applications)