

BS133N

Battery 12 V 65 Ah



Standard Features

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS133N

Battery 12 V 65 Ah

Specifications

| Electrical Characteristics | |
|-----------------------------|--------------------------|
| Nominal voltage | 12 V |
| Nominal capacity | 65 Ah |
| Internal approx. resistance | 10 mOhm |
| Charge / discharge | |
| Max. charge voltage | 13.8 VDC at +20°C |
| Max. charge current | 19.5A |
| Max. discharge current | 325 A |
| Temperature | |
| Charging temperature | 0 to +40°C |
| Discharging temperature | -15 to +50°C |
| General | |
| Product type | Sealed lead acid battery |
| Physical | |
| Physical dimensions | 350 x 166 x 174 mm |
| Net weight | 23.0 kg |
| Shipping weight | 23.0 kg |
| Material | ABS |
| Terminal type | MS bolt & nuts |
| Environmental | |
| Fire retardant | No |
| Operating temperature | 0 to +40°C |
| Storage temperature | -15 to +50°C |
| Standards & regulation | |
| Compliance | CE, RoHS 2, WEEE |
| Certification | VdS |

Ordering Information

| Part No. | Description |
|----------|--------------------|
| BS133N | Battery 12 V 65 Ah |