

DP721RTA

700 Series Conventional Multi Detector w/ Relay Output & Auto Reset

Preventing false alarms with self diagnostics

All Aritech 700 series smoke detectors continuously monitor their sensitivity and operational status. Background drift is daily compensated to maintain the original calibrated sensitivity within the required limits.

Once a day the detector performs a full diagnostic test that includes dynamically testing the sensing chamber and internal electronics. If a detector drifts out of sensitivity range or fails the internal diagnostics test, this is reported back to the panel and indicated on the detector with a yellow fault LED.

Maintenance friendly sensitivity level test mode

The 700 Series photoelectric detectors include a sensitivity test mode that may be activated by simply holding a magnet near the detector's test point. This initiates a self-diagnostic routine and provides visual indication if service is required. This test mode allows field sensitivity testing without the requirement for external meters or test gas.

Field cleaning and service

The photoelectric sensing chamber unclips from the detector for easy field cleaning and service. During regular maintenance the detector cover can be removed, the optical chamber removed and replaced by a low cost, new chamber. On power up the detector auto-calibrates and returns to normal operating mode without any further intervention.

The right detector for the right job

For a truly fast and broad-spectrum detection the DP721RTA offers both optical and heat sensors. The interaction of both the smoke and heat algorithms ensure a quick response to both flaming and smoldering fires.

All bases are provided with an integral locking tab for extra security if required. Bases are equipped with a shorting bar between IN and OUT that opens when the head is installed and that may be manually restored when removing the head. This simplifies cable continuity testing.

Note:

The DP721RTA must not be used in applications requiring compliance with commercial or residential fire standards such as EN54-5/EN54-7/EN54-29/CEA4021/EN14604. Always ensure compliance with local codes and standards.



Standard Features

- Automatic self diagnostics with dynamic full detector and sensitivity test
- Manual self diagnostic routine with visual sensitivity indication
- Field sensitivity testing without external meters
- Field exchangeable and disposable optical chamber
- High false alarm immunity
- Floating background with drift compensation
- Separate fire and fault LEDs
- 12-24VDC operation
- Polarity insensitive
- COM/NO/NC contacts for easy supervision on any system
- Automatic reset when event clears

DP721RTA

700 Series Conventional Multi Detector w/ Relay Output & Auto Reset

Specifications

General	
Status indication	White LED (red in alarm), Yellow LED (test & fault)
User interface	LEDs
Compatibility	Aritech conventional systems & Aritech conventional ZMUs
Reset voltage	<2.5 V max
Reset time	1 s
Connectivity	2-wire zone & relay
Electrical	
Operating voltage	8.5 to 33 VDC
Current consumption	100 µA (quiescent) <60 mA (in alarm)
Detection	
Detection principle	Optical light scatter and heat
Sensitivity	10%/m (+1.6%, -3.3%)
Zone length	Cable dependent
Rate-of-rise	8°C/min above 40°C
Output	
Output quantity	1
Output type and rating	Relay - NO/C/NC (2 A at 30 VDC, 1 A at 120 VAC)
Programmable	No
Remote alarm output	NA
Physical	
Physical dimensions	100 x 50 mm (Ø x H)
Net weight	112 g
Colour	Cloud white (RAL 9001)
Mounting type	Ceiling mount
Material (body)	Plastic
Environmental	
Vandal proof	No
Operating temperature	-10 to +60°C
Storage temperature	-10 to +70°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP43
Ambient temperature	+25°C
Standards & regulation	
Compliance	CE, REACH, RoHS 2, WEEE
Certification	CE

Ordering Information

Part No.	Description
DP721RTA	700 Series Conventional Multi Detector w/ Relay Output & Auto Reset Functionality
DB702	700 Series 6 Terminal Conventional 2-wire Base - 100 mm
DB702U	700 Series 6 Terminal Conventional 2-wire Base - 150 mm
211	(10 Pack) 400/500/700/2000 Replacement Chamber