

FE130MS

Eco Line magnetic lock 300 Kgf, monitored, surface mount

Description

Eco Line magnetic lock 300 kgs, monitored. Surface mounting.

Application

Medium security applications for internal and external doors. To be mounted inside external doors.

Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle rackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



Standard Features

- 300 kgf holding power
- Surface mounted
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Monitored changeover

FE130MS

Eco Line magnetic lock 300 Kgf, monitored, surface mount

Specifications

| General | |
|------------------------------------|------------------------------|
| Product type | Magnetic lock |
| Holding force | |
| Holding force kgf (Kilogram force) | 300 kgf |
| Holding force N (Newton) | 3000 |
| Monitoring & status | |
| Monitored | Yes |
| LED indicator | Yes |
| Door status switch | No |
| Monitored changeover | Yes |
| Magnetic bond sensor | Yes |
| Electrical | |
| Power supply value | 12 / 24 VDC |
| Current consumption | 440 mA (+/- 2,5% @ 13,5 V) |
| Physical | |
| Physical dimensions | 250 x 47 x 26 mm (W x H x D) |
| Colour | Aluminium |
| Finish | Vapour blasted aluminium |

Ordering Information

| Part No. | Description |
|----------|----------------------------------------------------------|
| FE130MS | Eco Line magnetic lock 300 Kgf, monitored, surface mount |