

# FE160MS

Eco Line magnetic lock 600 Kgf, monitored, surface mount

## Description

---

Eco Line magnetic lock, 600 Kgf, monitored, surface mounting

## Application

---

High security applications for internal and external doors. To be mounted inside external doors.

## Reliable Security

---

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle rackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

## Safe operation

---

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



## Standard Features

---

- 600 Kgf holding power
- Surface mounted
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Monitored changeover
- Mounts easily with a minimum of tools

# FE160MS

Eco Line magnetic lock 600 Kgf, monitored, surface mount

## Specifications

General	
Product type	Magnetic lock
Holding force	
Holding force kgf (Kilogram force)	600 kgf
Holding force N (Newton)	6000
Monitoring & status	
Monitored	Yes
LED indicator	Yes
Door status switch	No
Monitored changeover	Yes
Magnetic bond sensor	Yes
Electrical	
Power supply value	12 / 24 VDC
Current consumption	450 mA (+/- 2,5% @ 13,5 V)
Physical	
Physical dimensions	266 x 73 x 40 mm (W x H x D)
Colour	Aluminium

## Ordering Information

Part No.	Description
FE160MS	Eco Line magnetic lock 600 Kgf, monitored, surface mount