

## FE260-325

Door Holder, Universal Adjustable Tube, 400N, with Release Button, 325 mm

### General

The FE260-325 is a floor/wall mount door holder with a universal adjustable tube with a reach of 325 mm when used in 180° configuration and 300 mm used in 90° configuration. Which offers a 400N holding force and a release button.

### Magnet construction

The magnet is constructed with a pressed coil and anti-remnance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

### Adjustable

The “head” of the FE260-325 allow for two mounting options. The first being the 180° configuration, which is normally used when the door holder is mounted on the wall. In this configuration, the magnet is located “on-top” of the tube. And the second configuration being the 90° configuration, which is normally used when the door holder is mounted on the ground. In this configuration, the magnet is located on the “side” of the tube, as shown in the picture.

To allow for even more flexibility, the tube can also be cut shorter to match the exact distance required.

### Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals. - The base is predrilled in a practical, standard format for rapid mounting. - The door holder is supplied complete with a keeper plate, which offer angular adjustment.

### Approvals

The FE260-325 is fully approved according to EN1155.



### Standard Features

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Adjustable
- Keeper plate included

# FE260-325

Door Holder, Universal Adjustable Tube, 400N, with Release Button, 325 mm

## Specifications

Electrical	
Power supply type	24 VDC
Power consumption	1.6 W
Duty cycle	100%
General	
Holding force N (Newton)	400
Release button	Yes
Spark suppression diode	Yes
Reverse polarity protection	Yes
Physical	
Physical dimensions	80 x 90 x 300 mm (W x H x D) 90° setup 80 x 90 x 325 mm (W x H x D) 180° setup
Environmental	
IP rating	IP54 (Magnet) IP42 (Connection)
Standards & regulation	
Standards	EN1155

## Ordering Information

Part No.	Description
FE260-325	Door Holder, Universal Adjustable Tube, 400N, with Release Button, 325 mm
FE230	Door Holder, Surface Mount, 400N, with Release Button
FE235	Door Holder, Square Base, 400N
FE240	Door Holder, Flush Mounting, 400N
FE245	Door Holder, Wall Mount, 400N, with Release Button
FE250	Door Holder, Floor Mounting, 400N, with Release Button
FE260-175	Door Holder, Universal Adjustable Tube, 400N, with Release Button, 175 mm
FE260-475	Door Holder, Universal Adjustable Tube, 400N, with Release Button, 475 mm
FE290	Door Holder, Surface Mount, 400N, Mains Powered