

# MC352-4P-2S

## 4-Port Gigabit Ethernet to 2-Port SFP Industrial Media Converter

### Overview

The IFS® 4-Port Gigabit Ethernet to 2-Port SFP Industrial Media Converter is designed for the most demanding IP network applications offering the flexibility of SFP technology and wide operating temperature range. The MC352-4P-2S model provides full IEEE802.3-at (30w) PoE and serves as a PSE device.

### SFP Technology

This model converts 10/100/1000Base-T Ethernet on copper to 100Base-X or 1000Base-X fiber via Small Form-factor Pluggable (SFP) technology. The media converter can be custom configured to your exact system design specifications by utilizing a variety of IFS SFP Mini-GBIC modules. IFS SFP Mini-GBIC modules are available in a variety of versions from multi-mode or single mode fiber, 1 or 2 fibers and wide-temperature versions.

### Flexible Drop-and-Repeat or Redundant Path Operation

These models support 2 SFP ports that can easily be configured for either drop-and-repeat or redundant path operation. In drop-and-repeat mode, the unit operates like a 6-port switch and can be used as a repeater with an electrical drop or simply as an optical repeater/extender. In redundant path mode, the unit will quickly switch to the second SFP port as a redundant path if the primary optical path experiences an optical cable failure. Also, if the primary destination port link is down, the module will forward the data packet to the redundant path providing a highly fault-tolerant solution for mission critical IP applications.



### Caratteristiche standard

- 10/100/1000 Base-SX/BX/LX/LHX/ZX and 100 Base-FX/BX/LX
- 10/100/1000Base-T: 2-pair Cat. 5e/6 UTP cable, up to 100 meters
- Complies with IEEE 802.3at and is backwards compatible with IEEE802.3af
- Inserts 52VDC (30w) power on Category network cable
- 2 SFP slots provide for custom configuration
- Optical fiber and distance varies by SFP (ordered separately)
- Plug-n-play installation
- Slim IP30 metal enclosure
- DIN-rail or wall-mounting
- 12 to 48 VDC, redundant power with reverse-polarity protection
- Alarm relay output for port breakdown and power-failure alert
- Complies with IEC60068-2-xx standards for free-fall, shock and vibration
- Wide operating temperature range of -40°C ~ +75°C
- Protects non-PoE devices if accidentally connected

# MC352-4P-2S

## 4-Port Gigabit Ethernet to 2-Port SFP Industrial Media Converter

### Dati tecnici

Ethernet	
Data Rate	10/100/1000 Base-T
Throughput (packet per second)	1,488,000pps
Switch Architecture	Store-and-forward
Jumbo Packet Size	9K
Flow Control	Back Pressure for Half Duplex, Mode Pause for Full-Duplex Mode IEEE 802.3x
Connector	RJ-45 (Auto-MDI/MDI-X)
Cable Type and Distance	10Base-T: 2-pair UTP Cat. 3,4,5, up to 100 m (328 ft.) / 100Base-TX: 2-pair UTP Cat. 5e, up to 100 m (328 ft.) / 1000 Base-T: 4-pair UTP Cat. 5e, 6 up to 100m (328 ft.)
Fiber	
PoE Standard	IEEE 802.3af / 802.3at High Power over Ethernet / PSE
Power PIN Assignment	End-Span, (+) Pins 1 & 2; (-) Pins 3 & 6
Power Output per Port	52VDC 15.4 Watts or 52VDC 30 Watts
Data Rate	100Base-FX/BX/LX and 1000Base-SX/BX/LX/LHX/ZX
Connector	SFP (Mini-GBIC) port
Fiber Type and Distance	Varies by SFP module
LED Indicators & Controls	
Power/Status	Green/On – power
10/100/1000Base-TX port	Green/On – active port (TX/RX), Amber/On – PoE in-use
SFP (Mini-GBIC) port link	Green/On – link established
Electrical & Mechanical	
Power	48VDC (15.1 watts no PoE; 135.1W full load)
Enclosure	IP30 rated metal enclosure
Dimensions (H x W x D)	2.8 x 5.9 x 4.2 in. (72 x 152 x 107mm)
Weight	3.39 lbs. / 1539 grams
Environmental	
Operating Temperature	-40°C ~ +75°C
Storage Temperature	-40°C ~ +85°C
Relative Humidity	5% ~ 90% (non-condensing)
MTBF	> 50,000 hrs @ 25°C
Standards Compliance	
IEEE	IEEE 802.3 10Base-T / IEEE 802.3u 100Base-TX / 100Base-FX / IEEE 802.3ab 1000Base-TX / IEEE 802.3z 1000Base-SX/LX/BX / IEEE 802.3x Flow Control and Back Pressure
EMI	EN 55022 CLASS A / EN61000-3-2:2006 / EN61000-3-3: 1995+1A:2001+A2:2005
EMS	EN 55024:1998+A1:2001+A2:2003 / IEC 61000-4-2:2001 / IEC 61000-4-3:2008 / IEC 61000-4-4:2004 / IEC 61000-4-5:2005 / IEC 61000-4-6:2008 / IEC 61000-4-8:2001
Accessories	
PS48VDC240W-EU	48VDC@5A External Power Supply
PS48VDC240W-UK	48VDC@5A External Power Supply
PS48VDC240W-DIN	

### Come ordinare

Codice prodotto	Descrizione
MC352-4P-2S	4-Port Gigabit Ethernet to 2-Port SFP Industrial Media Converter