

PM812-G2

linear mode, boxed power supply, EN50131 grade 2 certified, 12VDC 1.5 A

Certified Gr.2

Suitable for use in systems designed to comply with EN50131-6:2008 to Grade 2 and Environmental Class II, requiring 17Ah standby battery capacity.

Protection

Comprehensive protection is built-in as standard including mains transient filtering, transformer thermal fuse, electronic output overload protection and fuses on the load and battery outputs.



Standard Features

- Fault signals for loss of mains, power supply fault and battery low voltage warning
- Battery deep discharge protection
- Tamper switch
- Protection against reverse battery connection
- Thermal protection of power circuitry
- Transformer thermal fuse
- Powder coated steel housing
- EN50131-6:2008 certified
- Powder coated steel housing

PM812-G2

linear mode, boxed power supply, EN50131 grade 2 certified, 12VDC 1.5 A

Specifications

Input voltage	230 VAC
Output voltage	13.8 VDC
Output current	
Mains	1.4 A
Battery for 12 hours	1.4 A with 17 Ah battery
Output Ripple	<220 mV pk – pk max @ 230 VAC
Max. battery size	17 Ah 12 V
Battery recharge time	< 72 hours to 80%
Deep discharge protection	Battery disconnect at 10.6 V battery terminal voltage
Protection	Reverse battery connection protection
Fuse	
Load	F2.0 A
Battery	F2.0 A
Operating temperature	-10 to +40°C
Storage temperature	-20 to +80°C
Housing (steel) powder coated	
	1.2 mm
Dimensions (W x H x D)	330 x 275 x 80 mm
Weight without battery	4.5 kg
Certifications	EN50131-6:2008 Environmental Class II

Ordering Information

Part No.	Description
PM812-G2	linear mode, boxed power supply, EN50131 grade 2 certified, 12VDC 1.5 A